



BACTERIOLOGICAL WATER ANALYSIS

COMPLETE INFORMATION BELOW:

Time Collected: ____:____ AM PM Date Collected: ____/____/____ Collector's Initials: _____
mm dd yyyy

Collected At: _____

Owner: _____

SELECT DESIRED METHOD(S) TO HAVE A COPY SENT BY AND OR RESULTS NOTIFICATION AND FILL OUT INFORMATION BELOW ACCORDINGLY:

MAIL EMAIL FAX PHONE

Name: _____ Phone: _____

Address: _____ Fax: _____

City: _____

State: _____ Zip: _____ Email: _____

Sampler's Remarks _____

LABORATORY TEST RESULTS (to be completed by LAB)

Safe (Coliform Absent) Unsafe (Coliform Present) Invalid (Submit another Sample)

Fecal / E Coli. Present Reason: _____

Fecal / E Coli. Absent _____

RECEIVED	IN	OUT
Date: ____/____/____ INIT	Date: ____/____/____ INIT	Date: ____/____/____ INIT
Time: ____:____ <input type="checkbox"/> AM <input type="checkbox"/> PM	Time: ____:____ <input type="checkbox"/> AM <input type="checkbox"/> PM	Time: ____:____ <input type="checkbox"/> AM <input type="checkbox"/> PM

SAMPLING INSTRUCTIONS

Routine bacteriological samples should be collected from a representative location, (a sink or spigot that is routinely used for drinking water). Do not sample from hoses, leaky faucets, or utility sinks. Bacteria can grow in these areas. If you are not sure where to collect the samples, contact the Jackson Water Utility for additional information at (262) 677-0707 ext. 712. Samples must be received at the Jackson Public Works/Utility building (W194N16660 Eagle Drive) within 24 hours of sample collection.

Samples will only be accepted Monday through Thursday, 7:30 AM to 3:00 PM. No samples will be accepted on Fridays, or the day before Village holidays.

1. Select a clean faucet and remove faucet aerators or filter devices. Water should be hard water source and not softened by any mechanical means. Avoid plastic, swing, and goose-neck faucets.
2. Fill out the sample form while running cold water for several minutes.
3. Sterilize the tap or faucet using a propane or butane torch. Hold the flame beneath the tap or faucet opening for 20 seconds. Be certain the faucet contains no plastic internal parts that could become damaged due to heat. Move the flame continuously to prevent damage to the faucets finish. The Village of Jackson is not liable for any damages that may occur.
4. Reduce the flow to a pencil-thin stream to prevent splashing, for about 5 minutes before collecting the sample. Remove the plastic cap seal and collect the sample directly into the bottle.
5. **DO NOT RINSE THE CONTAINER, OR USE AN INTERMEDIATE CONTAINER, OR CONTAMINATE THE INSIDE OF THE CAP OR BOTTLE WITH YOUR HANDS.**
6. Fill the bottle to the 100ml line leaving 1 inch of air space.
7. Replace cap securely and take the sample, along with the paperwork to the Jackson Public Works/Utility building during the time listed above. Do not subject sample to freezing or excessively hot conditions.